

Sucrogen BioEthanol

Isopropanol

Not Just a Rubbing Alcohol ...

Isopropanol is an alcohol that is colourless and miscible in water. It is used to make countless industrial and consumer products. Sucrogen BioEthanol maintain strict quality and testing procedures to ensure that the Isopropanol provided meets all required specification limits when it arrives at your site.



Markets and Applications

- Rubbing Alcohol
- Printing Inks
- Surface Coatings
- Antiseptic
- Cleaning Products
- Cosmetics
- Antifreeze
- Pharmaceuticals

Available Grades

- Industrial
- ASTM
- BP
- AR

Packaging

Available as

- Bulk deliveries varying amounts*
- IBC's*
- 160kg drums
- 16kg pails

**minimum delivery size or other constraints may apply*

Specifications

Parameter	Specification
Purity	99.8% by weight (min)
Colour	10 Hazen units (max)
Water Content	0.2% by weight (max)
Density	0.788 – 0.790 kg/L @ 15°C
Acidity	0.002% by weight (max) acetic acid
Distillation Range	1.5°C (max) including 82.3°C
Boiling Point	82.4°C
Flash Point	12°C (tag closed cup)
Evaporation Rate	230



For further information on the Sucrogen BioEthanol range of products, please contact

Sucrogen BioEthanol Pty Ltd
664 Lorimer Street
Port Melbourne
Vic 3207, Australia

t: 1800 819 618
f: 1800 647 260
www.sucrogen.com
Email: bioethanol@sucrogen.com
ABN: 85 009 660 191