

Sucrogen BioEthanol

n-Propanol Solvent for Printing

n-Propanol, or often called “propanol”, is a good solvent used for a wide variety of resins. It is used primarily as a printing ink solvent, but is also used as a flavouring agent.

Being partnered with Oxea, one of the largest manufacturers globally, we can consistently provide availability in all supply climates.



Markets and Applications

The use for n-Propanol is in the printing, ink and surface coatings markets.

Specifications

Parameter	Specification
Purity	99% by weight (min)
Colour	10 Hazen units (max)
Water Content	0.1% by weight (max)
Density	0.807 – 0.810 kg/L @ 15°C
Acidity	0.003% by weight (max)
Distillation Range	2.0°C (max) including 97.2°C
Boiling Point	97.4°C
Flash Point	27°C
Evaporation Rate	220



Packaging

Available as

- Bulk deliveries varying amounts*
- IBC's*
- 180kg drums
- 18kg pails

**minimum delivery size or other constraints may apply*



For further information on the Sucrogen BioEthanol range of products, please contact

Sucrogen BioEthanol Pty Ltd
664 Lorimer Street
Port Melbourne
Vic 3207, Australia

t: 1800 819 618
f: 1800 647 260
www.sucrogen.com
Email: bioethanol@sucrogen.com
ABN: 85 009 660 191